
INERUgged

Vehicle PC W/807

- Equipped with high-performance ARM octa-core processor and Android 12 OS, up to 4GB+64GB capacity.
- 8-inch screen with 700-Nits high definition display, multiple-point touch panel and customized keys, ensuring outdoor worker visibility.
- 4G LTE, dual-band Wi-Fi and Bluetooth 5.2 connectivity. Multi-satellite systems of GPS/Glonass/Beidou, with vehicle mushroom antenna for real-time tracking to your vehicle and asset management.
- With aviation plug charging interface, switchable for cigarette lighter interface or Φ4.0 power port, and the external 9V-36V DC wide voltage module is optional.
- Supports the battery-free mode, another optional 3.7V/2000mAh capacity battery.
- Available multiple navigation plug interfaces, and also supports USB/DB9/LAN/CAN and other interface extensions.
- Two bracket mounting methods, VESA and RAM are suitable for almost any vehicle-mounted workplaces.
- IP65 dustproof and waterproof, morphed to endure outdoor applications prone with shock, vibration and extreme temperature.



ARM octa-core processor



Android 12 Operating System



8-inch screen



1000cd/cm2




Dual frequency Wi-Fi



GPS/GLONASS/ Beidou



Stable power supply



Rich interface extensions



VESA/RAM



IP65



Vehicle PC V80T

INERUgged

Specifications



ARM octa-core processor





Memory

RAM: 4GB LPDDR4X ROM: 64GB UFS



Type: LCD Size: 8 inch 16:10 Resolution: 800*1280 IPS Brightness: 1000cd/m²



Touch Pannel

5 points Capacitive



Dimension/Weight

218.1*154.5*23.0mm **TBD**



Buttons

Power *1 Volume Adjustment Key (+) *1 (F1 Key) Volume Adjustment Key (-) *1 (F2 Key) Customizable *1 (F3 Key) Customizable *1 (F4 Key)



Speaker

1.5W *1, Single horn (Maximum 2W)



Battery

Optional, Built in polymer lithiumion battery 2000mAh/3.7V



WIFI

WIFI 802.11(a/b/g/n/ac) Dual frequency 2.4G+5.0G (5.1G+5.8G)





WAN

4G



GPS

GPS/GLONASS/Beidou



Optional



□ I/O Interface

SIM card slot (optional) MICRO-SIM x 1 Standard USB-A port / Data transmission Power interface PORT1 (M12-12) (optional) 100M network port PORT2 (M12-12) (optional) RS232 *1+RS232/RS485 (standard) *1 PORT3 (M12-12) (optional) USB 2.0 *1+USB 2.0 (default) /CAN*1+USB 2.0 (default) /CVBS*1



Rugged Features

Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C ±8kV contact discharge, ±15kV air discharge Humidity: 95% Non-Condensing



Adapter

12V 4A DC φ4.0 Adapter

* The technical specifications of this product are subject to change without prior notice



Tel: 400-830-4882

www.onerugged.com

□ inquiry@onerugged.com

Room 401, Building C, Chaojie Industrial Park, No. 1 Guanghui Road, Jinsha Community, Kengzi Street, Pingshan District, Shenzhen, China